

GMP ROLL COMPACTOR MODEL : LMRC

SALIENT FEATURES

- GMP Model with Contact parts of SS 316
- Compacting Roll Surface – Corrugated/ knurled/ Briquetted/ Smooth
- ACVFD for Main and Feeder Screw Motors

TECHNICAL SPECIFICATION : *

Model	LMRC – 50	LMRC – 100
Roll Size (mm)	200 Dia. X 50 Width	200 Dia. X 70 Width
Max. Output (Kg. /hr.) (Depends on Roll surface & Material characteristics)	50	100
Main Electric Motor	5hp, 415V, 50 Hz. 3 ph.	
Roll Surface (Selection of Rolls are depend on materials)	Corrugated (Std.) / Smooth / Knurled / Briquetted	
Main Roller Speed (rpm)	6 – 25	6 – 25
Feed screw speed (rpm)	10-50	10-50
Overall Dimensions (cm)	110 X 120X 195H	



* Due to continuous process of upgradation, we reserve all rights of alteration without any prior intimation.

- * cGMP Model.
- * Easy Operation.
- * Easier cleaning procedure.
- * Extremely Quite Operation.
- * Complete Paint Free.

Use of Roll Compactor in various Industry:

- * To optimize Bulk Density of Products.
- * To optimize particle hardness.
- * To optimize uniformity of granules sizes while granulating the compacted flakes.
- * To reduce volume to reduce transportation costs.

For more details, please send your enquiry or, contact us.
We will be happy to hear from you..

LABAID MACHINERY



G.I.D.C., Odhav, Ahmedabad
Gujarat - 382415, India
www.labaidmachinery.com



Call : + 91 7862983913



info@labaidmachinery.com
machinerylabaid@gmail.com
labaidmachinery@yahoo.com